



225K UNIT

Service > Hydraulic Workover > Equipment

225K QUICK RIG



Fast, reliable and safe best describe the 225K Snubbing Unit's key benefits. The compact design is ideally suited for moving quickly from site to site its rapid rig up time make it a very efficient option. Easily rigged up in two lifts this versatile snubbing unit is ideal for onshore applications and is extremely well suited for through tubing live well work like; wireline/coil tubing fishing, velocity strings and well clean-outs.

The Practical slim line design of the jack has resulted in faster jack speed and increasing the trip time ensuring less time is spent on the well; this is significant, as it reduces cost. A Special Annular BOP window enables quick annular rubber change-outs without the need of rigging down the unit.

Advantages & Characteristics:

- Trailer mounted / Installation in two lifts
- 7-1/16" BOP stack with stripping annular
- Flexible BOP stack heights
- Mobile
- Excellent cost/quality ratio
- Multi-purpose application

Technical Data

225K HWO/Snubbing unit

Max. pull capacity	225,000 lbs	100 ton
Max. push capacity	90,000 lbs	40 ton
Rotary torque	6,000 ft. lbs @ 140RPM	8,000 Nm @ 140RPM
Stroke	10 ft.	3 m
Through bore	11 1/8" (Snubbing)	283 mm (Snubbing)
	11 1/8" (HWO)	283 mm (HWO)
Gin Pole	2 x 3,000 lbs	2 x 1,3 ton
	2 x 8,000 lbs	1 x 3,5 ton (main winch)
Unit total weight	57,000 lbs	26 ton



Get your wells fixed quickly – Speed up work!
Exploit the benefits of our trailer mounted quick rig units

www.bpc.nl