



# HWO/SNUBBING UNIT 460K

Service > Hydraulic Workover > Equipment



The reliable and flexible 460K HWO/Snubbing Unit has been designed for all well situations: live/dead, onshore/offshore. The 460K satisfies your needs for high quality, safe and efficient Snubbing or Workover operations in any environment.

The jointed work string is handled by means of 4 hydraulic cylinders (10 ft. stroke). The use of hydraulic cylinders allows perfect control over work string movements and makes it easy to use all types of downhole tools.

## Advantages & Characteristics:

- Unique “Slip bowl Interlock System”
- Small footprint
- Flexible
- Mobile
- Excellent cost/quality ratio
- Multi-purpose application

## Operational activities:

- Handling all types of completions
- Live/Dead well operations
- Packer setting/milling
- Well clean out
- Live well Fishing operations
- Underbalance drilling/milling/liner installation
- Remedial operations
- Installation of velocity strings
- Casing Leak repair
- P&A and Re-abandonment

## Technical Data

<b>Max. pull capacity</b>	460,000 lbs	208 tons
<b>Max. push capacity</b>	210,000 lbs	95 tons
<b>Rotary torque</b>	22,000 ft.lbs	29,000 Nm
<b>Stroke</b>	10 ft	3,04 m
<b>Through bore</b>	14”	355 mm
<b>Slip bowls</b>	460,000 lbs	208 tons
<b>Gin Pole</b>	10,000 lbs	4,50 tons
<b>Unit total weight</b>	56,000 lbs	26 tons

## Cost efficient work over

Exploit the benefits of our hydraulic workover services

[www.bpc.nl](http://www.bpc.nl)