



## UNITCARD

# 460K HWO/Snubbing unit

Service -> Hydraulic Workover -> Equipment



The reliable and flexible 460K HWO/Snubbing Unit has been designed for all well situations: live/dead, onshore/offshore. The 460K satisfies your need for high quality, safe and efficient Snubbing or Workover operations in any environment.

The jointed work string is handled by means of 4 hydraulic cylinders (10 ft. stroke). The use of hydraulic cylinders allows perfect control over work string movements and makes it easy to use all types of downhole tools.

### Technical Data

Max. pull capacity	460,000 lbs	208,000 kg
Max. push capacity	210,000 lbs	95,000 kg
Rotary torque	22,000 ft lbs	29,000 Nm
Stroke	10 ft	3 m.
Through bore	14"	355 mm
Slip bowls	460,000 lbs	208,000 kg
Gin pole	10,000 lbs	4,500 kg
Unit total weight	56,000 lbs	26,000 kg

### Operational Activities:

- Handling all types of completions
- Live/Dead well operations
- Live well Fishing operations
- Packer setting/milling
- Remedial operations
- Well clean out
- Installation of velocity strings
- Packer setting/milling
- Casing Leak repair
- P&A and Re-abandonment

### Advantages & Characteristics:

- Simple and cost efficient
- Small footprint
- Flexible
- Mobile
- Excellent cost-quality ratio
- Multi-purpose application